

表 2

外壳编号	额定电压 V	降额电压 V	标称电容量 μF	室温损耗 %	负温阻抗 -55°C 100Hz Ω	外壳编号	额定电压 V	降额电压 V	标称电容量 μF	室温损耗 %	负温阻抗 -55°C 100Hz Ω	外壳编号	额定电压 V	降额电压 V	标称电容量 μF	室温损耗 %	负温阻抗 -55°C 100Hz Ω				
1	6.3	4	22	8	150	1	25	16	6.8	4.6	300	1	100	63	1.5	5	1400				
1			33	9	100	1			10	4.6	220	1			2.2	5	1100				
1			47	18	80	1			15	6.5	175	1			3.3	6	700				
1			68	20	60	1			22	8.3	140	1			4.7	6	500				
2			100	30	60	2			33	20	110	2			6.8	8	350				
2			150	35	50	2			47	15	80	2			10	10	260				
3			220	45	50	3			68	20	75	3			15	15	175				
3			330	50	45	3			100	25	60	3			22	12	130				
4			470	85	40	4			150	50	55	4			33	20	100				
5			680	90	35	5			220	50	55	5			47	25	65				
6			1000	100	25	6			330	50	45	6			68	25	65				
6			1200	144	20	6			470	60	40	6			100	25	60				
1	10	6.3	15	6	200	1	40	25	4.7	4.5	450	1	125	75	1.0	6	1800				
1			22	7	175	1			6.8	4.5	350	1			1.5	6	1400				
1			33	15	125	1			10	4.5	260	1			2.2	6	1100				
1			47	15	100	1			15	9	175	1			3.3	6	700				
2			68	25	80	2			22	10	140	2			4.7	6	500				
2			100	25	60	2			33	12	110	2			6.8	8	350				
3			150	45	55	3			47	15	80	3			10	13	260				
3			220	45	45	3			68	20	75	3			15	13	170				
4			330	70	40	4			100	35	65	4			22	20	150				
5			470	75	35	5			150	35	50	5			33	20	120				
6			680	80	30	6			220	40	45	6			47	20	90				
6			1000	90	25	6			330	45	35	6			68	23	70				
1	16	10	10	5.7	200	1	63	40	2.2	4	1100										
1			15	5.7	155	1			3.3	4.5	700										
1			22	10	140	1			4.7	5	500										
1			33	12	90	1			6.8	5	350										
2			47	18	80	2			10	8	260										
2			68	20	75	2			15	8	175										
3			100	35	65	3			22	12	140										
3			150	35	60	3			33	12	90										
4			220	60	55	4			47	25	80										
5			330	60	45	5			68	25	80										
6			470	60	40	6			100	25	60										
6			680	70	35	6			150	28	50										