

表 1

额定电压 V		6.3	10	16	25	40	63	100	125		
降额电压 V		4	6.3	10	16	25	40	63	75		
外形尺寸 mm		最大 重量 g	标 称 电 容 量 μF								
D	L		22	15	10	6.8	4.7	2.2	1.5	1.0	
5	10	3	33	22	15	10	6.8	4.7	2.2	1.5	1.0
			47	33	22	15	10	6.8	3.3	2.2	1.5
			68	47	33	22	15	10	4.7	3.3	2.2
									6.8	4.7	3.3
5	14	4	100	68	47	33	22	10	6.8	4.7	
			150	100	68	47	33	15	10	6.8	
6	16	5	220	150	100	68	47	22	15	10	
			330	220	150	100	68	33	22	15	
8	16	7	470	330	220	150	100	47	33	22	
8	22	10	680	470	330	220	150	68	47	33	
10	22	14	1000	680	470	330	220	100	68	47	
10	25	17	1200	1000	680	470	330	150	100	68	
10	30	25		1200	1000	680	470	220	150		
						1000	680	220	150	220	

注：带绝缘外套后 D 增加 0.3 mm。电容量大于 1200 μF 可提供组合式产品，技术要求可商定。

表 2 频率为 100Hz 测量

额定电压 V	6.3	10	16	25	40	63	100	125
标称容量 μF	损 耗 角 正 切 %							
1~4.7					6	6	6	6
6.8				8	8	8	8	8
10			10	8	8	8	10	15
15		15	10	10	10	10	18	15
22	15	15	10	10	20	18	15	23
33	20	15	12	20	12	12	25	23
47	25	15	20	15	25	25	28	20
68	30	30	20	30	20	25	20	23
100	35	20	35	25	35	20	25	
150	40	50	35	50	35	28	25	
220	70	45	60	50	30	40	35	
330	50	70	70	40	45			
470	85	75	50	50	50			
680	80	65	70	50	70			
1000	90	80	90	90				
1200	90	90						