

表 1

额定电压 V		10	16	25	40	63	100	125	
降额电压 V		6.3	10	16	25	40	63	75	
外形尺寸 mm		最大 重量 g	标 称 电 容 量 μF						
D	L								
5	14	4.0	33	22	15	10	4.7	3.3	2.2
			47	33	22	15	6.8	4.7	3.3
6	16	5.0	68	47	33	22	10	6.8	4.7
			100	68	47	33	15	10	6.8
8	16	7.0	150	100	68	47	22	15	10
			220	150	100	68	33	22	15
8	22	10.0	330	220	150	100	47	33	22
10	22	14.0	470	330	220	150	68	47	33
10	25	17.0	680	470	330	220	100	68	47

注：带绝缘外套后 D 增加 0.3 mm。

表 2 频率为 100Hz 测量

额定电压 V	10	16	25	40	63	100	125
标称容量 μ	损 耗 角 正 切 %						
1~4.7					8	8	8
6.8					8	10	10
10				10	8	10	15
15			10	10	10	15	15
22		10	12	20	18	15	20
33	15	12	20	20	20	20	20
47	15	20	20	20	25	25	21
68	30	20	25	25	25	25	
100	20	35	31	35	25		
150	50	35	50	35			
220	45	60	50	30			
330	70	70	40				
470	75	50					
680	65						